

Integrated seedbed cultivators

CD 300/400



www.kuhn.com



be strong, be **KUHN**

CD**300****400**

SEEDBED PREPARATION IN LIGHT CONDITIONS

The CD tine harrow combinations are designed to prepare your seedbeds in light, sandy, loamy or limey-clay soils. They can also be used for spring turning after winter ploughing. Clearly economically beneficial, the two models provide an effective alternative in terms of work in all situations where a power harrow is not required.

WITH CD 300 AND 400 SEEDBED CULTIVATORS YOU GAIN:

- speed for increased daily output,
- in maintenance costs,
- in compatibility with most KUHN driven tools.

NO COMPROMISE WITH STRENGTH

KUHN has made no compromise on robustness on the 3 m as well as on the 4 m CD seedbed cultivators. The hitch frames are the same as on power harrows. Designed for intensive use or high-speed work!





WHAT MAKES ALL THE DIFFERENCE!

1. THREE ROWS OF TINES

- The CD tine cultivators can be fitted with three rows of tines. This setting is recommended for fine tilth soil preparation.
- The use of dual wheels and a front packer provides further improvement with regards to soil preparation and even soil packing.
- You also have the possibility to use tines on two rows and add a hydraulically adjustable levelling bar. This is available as option.

2. VERSATILITY: MONEY-SAVING!

Most of the power harrow equipment can be transferred onto CD tine cultivators: track eradicators - Packer, Maxipacker or Packliner rollers - hydraulic lift linkage. Significant savings for the user!



CD 300 400

CD FITS TO YOUR KUHN DRILLS

Integrated tine cultivators can be used with all INTEGRA and SITERA mechanical seed drills as well as VENTA EC and LC pneumatic seed drills currently in use. INTEGRA seed drills can be taken in and retrofitted with a link providing contact with the roller arms. If you wish to adjust the tines, there is no need to alter the seeding depth at the same time.



Technical specifications

Integrated seedbed cultivators

	CD 300	CD 400
Working width (m/ft)	3.00/9'10	4.00/13'1
Number of tines	2 rows: 19 3 rows: 24	2 rows: 25 3 rows: 32
Hitch frame	cat. 2 and (3*)	cat. 3 and (2*)
Weight (kg/lbs), approx., with PACKER PK2 roller	2 rows: 800/1763 3 rows: 850/1874	2 rows: 1175/2590 3 rows: 1240/2733
Weight (kg/lbs), approx., with MAXIPACKER roller	2 rows: 825/1818 3 rows: 880/1940	2 rows: 1195/2634 3 rows: 1260/2777
Depth control by roller	PACKER PK2, MAXIPACKER, PACKLINER or STEELLINER (possibility of Maxicrumbler but only with lift linkage attached seed drill)	
Working speed (km/h)	from 5 to 14 km/h depending on conditions	


*Hitch pins on request

Optional equipment CD: front levelling bar - tractor wheel track eradicators - adaptation parts for INTEGRA seed drill - kit comprising housing with PTO shaft for mechanical VENTA LC and EC blower drive - housing with drive for VENTA LC blower - rear hydraulic lift linkage - side marker kit mounted on CD - tractor hydraulic equipment: one double acting valve for the front levelling bar.

For more information about your nearest KUHNS dealer, visit our website www.kuhn.com



Visit us on our YouTube channels.



Your KUHNS dealer

www.kuhn.com

KUHN SAS

4 Impasse des Fabriques - BP 50060 - F-67706 Saverne CEDEX - FRANCE

KUHN NORTH AMERICA, INC.

1501 West Seventh Avenue - Brodhead, WI 53520 - USA

KUHN FARM MACHINERY PTY. LTD

313-325 Foleys Road - Deer Park, VIC, 3023 - AUSTRALIA

KUHN FARM MACHINERY (U.K.) LTD

Stafford Park 7 - GB TELFORD/ SHROPS TF3 3BQ

Information given in this document is only for information purposes and is non-contractual. Our machines are in compliance with regulations in force in the country of delivery. In our literature, and for improved illustration of certain details, some safety devices may not be in operating position. When operating these machines, these devices **must** be in position in accordance with the requirements indicated in the operator's manuals and pre-delivery instructions. RESPECT THE ROAD REGULATIONS IN FORCE AS WELL AS THE tractor gross vehicle weight rating, its lift capacity and maximum load per axle and tyres. The tractor front AXLE load must always comply with the regulations of the country of delivery (In Europe, it must reach minimum 20 % of the tractor net weight). We reserve the right to change any designs, specifications or materials listed without further notice. Machines and equipment in this document can be covered by at least one patent and/or registered design. Trademarks cited in this document may be registered in one or several countries.

Also find KUHN on  